



- 1260 Box Capacity
- Mobile Body
- Glass Doors
- Standard Key Lock

MEDSTOR^{MAX}

MS-IOL1260

INTRAOCULAR LENS CART

Features:

- Unmatched quality of construction — built to last using professional grade design and manufacturing for medical-grade applications
- Integrated, recessed side push handles so cabinet can stack flush with walls or other cabinets — we don't use easily misplaced removable handles or bulky exterior hardware.
- Key lock with two keys for lockable, secure storage of supplies
- Features a true 24" interior cabinet depth for storage of up to 1260 IOL boxes
- Six pull-out drawer shelves with adjustable dividers — ideal for medical supplies used in surgery centers and operating rooms
- Double doors can swing up to 270 degrees for easy access
- Glass windows allow for visibility of supplies and inventory
- Ball-bearing full extension drawer slides
- Industry best 5" quiet rolling Tente® casters for superior mobility - one steering and one braking caster
- Cabinet is delivered fully assembled

Engineered &
Manufactured
in the U.S.



Color shown in Hammertone Gray. More than 20 additional colors are available.

Assembled Cart Dimensions:

- 55.6" H x 42" W x 27.8" D
(141.2 cm H x 106.7 cm W x 70.6 cm D)
- Cart net weight: 375 pounds (170.1 kg)
- Approximate shipping weight: 490 pounds (222.3 kg)
- Approximate Shipping Dims: 65" H x 49" W x 39" D (165.1cm x 124.5cm x 99.1cm)

Warranty: 12-Year Limited Manufacturer's Warranty,
1-Year Limited Warranty on any bought-out parts

Mobile IntraOcular Lens Storage Cart, Three Quarter Height Cabinet, Six Drawers, Glass Doors, Standard Key Lock

Attractive, secure storage for IntraOcular lenses. Provides mobility and is compatible with multiple brands and sizes of IOL boxes including Alcon, Bausch and Lomb, Rayner, and Abbot Medical Optics.

HARLOFF
INNOVATING STORAGE FOR CARE

View similar products online at
<https://www.harloff.com/product-category/intraocular-lens-carts/>

Toll Free: (800) 433-4064 • medicalsales@harloff.com
www.harloff.com • Ph: (719) 637-0300